

VISITOR INTEGRAL



Anti slip overshoe with safety cap and anti-puncture sole



REF « VIT »

- Composition: Rubber + aluminium/titanium toe cap + steel sole
- Professional use: Slip resistance, toes and soles of the feet protection. Secure moves in the work place.
- ✓ **Anti-puncture sole made of steel**
- ✓ **Toe cap made of aluminium/titanium. Ultra light!**
- ✓ **Outstanding grip coefficient**
- ✓ **Multidirectional straps : secure hold of the foot**
- ✓ **Only 4 sizes to cover from 34 to 47**
- ✓ **Color code to track sizes**
- ✓ **Can be adapted to most kind of footwear**
- ✓ **Reusable**
- ✓ **Mixed Tiger-grip® sole for indoor and outdoor use**

Certifications

EUROPEAN DIRECTIVE
89/686/CE

Personal Protective Equipment



EUROPEAN STANDARDS

CE Certification:

0075/1344/161/01/18/0113

- NF EN ISO 20345 / 2011
- NF EN 12568
- NF EN 13287
- Oil resistance (FO)



CE PPE CERTIFIED Risk II

Certified Organism:

CTC N° 0075/69367 Lyon - France



AMERICAN STANDARDS

Certification in progress

● NF EN 13287 – Anti slip properties

Certification SRC : SRA + SRB

SRB :Anti-slip coefficient on steel floors with glycerin

SRA: Anti-slip coefficient on ceramic floors with detergent

Surface	Contact with	Standard ISO 13287	VISITOR INTEGRAL results
Steel	Oil	SRB = 0.18	+170 % = 0.49
Ceramic	Detergent	SRA = 0.32	+53% = 0.49

● NF EN 12568 – Toe cap resistance and antipuncture tests :

- × Cap: resistance against crushing under max load of 1500 DaN
- × Cap : 200 joules resistance
- × Puncture resistance

Antistatism: The overshoe meets antistatic and ESD properties.

The shoe and overshoe combination must necessarily be tested by the user

Sizes



	S				M				L			XL		
EU Sizes	34	35	36	37	38	39	40	41	42	43	44	45	46	47
UK Sizes	1	2	3	4	5	6	6,5	7	8	9	10	10,5	11	12
US Woman	4	5	6	7	7,5	8	8,5	9,5	10	11				
US Man					5,5	6	7	8	8,5	9,5	10	11	11,5	12,5

For a proper use of the overshoes, it is important to ensure that the overshoes fit neatly over the user's footwear

Storage and maintenance



- Hand washable - Let them dry naturally
- Store in a dry place, away from temperature variation
- Do not use below a temperature of -20°C.

Design and manufacturing : TIGER-GRIP ENGINEERING

✉ contact@tigergrip.com



120, rue Fornier
31700 BEAUZELLE, France



+ 33 5 34 60 56 56

www.tigergrip.com